

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11)

EP 0 040 373 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
25.11.1981

(51) Int. Cl.: F23N 05/24, F23N 03:04

(21) Application number: 81103517

(22) Date of filing: 08.05.1981

Patent published on CD-Rom:
ESPACE 81/025 ESP81025
FIRST 81/002 MIFT1981002

(84) Designated Contracting States:
AT BE CH FR GB IT LI NL SE

(30) Priority: 19.05.1980 DE 3019010
23.12.1980 DE 3048745

(71) Applicant: SAMSON AKTIENGESELLSCHAFT

(72) Inventors:

, Erb, Helmut, Ing. grad.
, Leese, Werner, Ing. grad.

(54) Combustion regulator

(57) The invention is with respect to a fail-safe system for stopping damage to water boilers, whose thermostats are not in working order. In an automatic combustion control system of the sort having an elastic thermostat bellows element placed within an outer shell within the water space of a boiler and joined by a chain or the like with the air door for controlling the air inlet rate at some point in the connection between the thermostat element and the door, there is a temperature-sensitive part, for example in the form of a plug of fusible metal or collapsing material, or in the form of a soldered joint using a special fusible solder. In one form of the invention, this temperature-sensitive part may take the form of a ring of temperature-sensitive material placed at one end of a spring which is forced together on the temperature increasing. On damage to the thermostat element, the one end of the spring will no longer be supported so that the spring will no longer take effect and so let the air door be moved down under its own weight into the shut position. In a further form of the invention, a body of temperature-sensitive material is placed between a rod, acting on one end of the thermostat element and a turning head which is used for making adjustment in the desired temperature. In a further form of the invention, the temperature-sensitive part takes the form of a plug of

EP 0 040 373 A1

temperature-sensitive material between the end of a gripping screw in a jointpiece and a turning rod acted upon by said screw. In a still further form of the invention, the temperature-sensitive part takes the form of a bimetallic wing, which is unhooked from a jointpiece on being heated to a limit temperature. As part of a still further form of the invention, a guide roller for a chain joining the thermostat with the air door is fixed to the side of the boiler by way of fusible solder, this taking the form of the temperature-sensitive part.

12

EUROPÄISCHE PATENTANMELDUNG

②¹ Anmeldenummer: 81103517.9

⑤ Int. Cl.³: F 23 N 5/24
F 23 N 3/04

②② Anmeldetag: 08.05.81

③① Priorität: 19.05.80 DE 3019010
23.12.80 DE 3048745

④3 Veröffentlichungstag der Anmeldung:
25.11.81 Patentblatt 81/47'

Ⓐ Benannte Vertragsstaaten:
AT BE CH FR GB IT LI NL SE

71 Anmelder: SAMSON AKTIENGESellschaft
Welsmüllerstrasse 3
D-6000 Frankfurt am Main(DE)

72 Erfinder: Erb, Helmut, Ing. grad.
Emmastrasse 3
D-6050 Offenbach/Main(DE)

72 Erfinder: Leese, Werner, Ing. grad.
Spechtstrasse 9
D-6078 Gravenbruch Neu-Isenburg 2(DE)

74 Vertreter: Eitner, Edmund F., Dipl.-Ing.
Schlotthauer Strasse 3
D-8000 München 90(DE)

⑤④ Feuerungsregler.

(57) Feuerungsregler zur Regelung der Vorlauftemperatur von Heizkesseln od.dgl. mit einem von der Kesseltemperatur beeinflussbaren Ausdehnungsthermostaten (2), der in einem mit dem Heizkessel verbundenen Reglergehäuse (30) angeordnet ist und über ein in oder an dem Reglergehäuse (30) gelagertes Hebelgestänge (81) od.dgl. entgegen der Wirkung einer Feder-(6) oder Gewichtskraft die Zug- oder Feuerklappe (10) od.dgl. des Heizkessels steuert, wobei in oder an dem Reglergehäuse (30) an einer der Temperatur des Heizkessels ausgesetzten Stelle ein in seiner Wirkung temperaturabhängiges Organ (15) oder Bauelement angeordnet ist, welches bei Überschreitung einer vorgegebenen, an dieser Stelle auftretenden Temperatur die Regelsteuerung der Zug- oder Feuerklappe unwirksam macht und eine selbsttätige Schließung dieser Klappe (10) ermöglicht.

